## UN/SCEGHS/3/INF.5/Add.6

Sub-Committee of Experts on the Globally Harmonized System of Classification and Labelling of Chemicals (Third session, 10-12 July 2002)

**DRAFT GHS** 

**ANNEX 2** 

UN/SCEGHS/3/INF.5/Add.6 (Annex 2) page 2

[Blank page]

## ANNEX 32

### CLASSIFICATION AND LABELLING SUMMARY TABLES

UN/SCEGHS/3/INF.5/Add.6 (Annex 2) page 4

[blank page]

### **A2 - CLASSIFICATION AND LABELLING SUMMARY TABLES**

#### **A2.1** Explosives (see Chapter 2.1 for details)

Hazard category	Criteria	Hazard communica	tion elements
Division 1.1	According to the results of the test in Part I of the Manual of	Symbol	
	Tests and Criteria.	Signal word	Danger
		Hazard statement	Explosive; mass explosion hazard
Division 1.2	According to the results of the test in Part I of the Manual of	Symbol	
Division 1.2	Tests and Criteria.	Signal word	Danger
		Hazard statement	Explosive; severe projection hazard
Division 1.3	According to the results of the test in Part I of the Manual of Tests and Criteria.	Symbol	
		Signal word	Danger
		Hazard statement	Explosive; fire, blast or projection hazard
Division 1.4	According to the results of the test in Part I of the Manual of Tests and Criteria.	Symbol	1.4
		Signal word	Warning
		Hazard statement	Fire or projection hazard
Division 1.5	According to the results of the test in Part I of the Manual of	Symbol	1.5
Division 1.5	Tests and Criteria.	Signal word	Warning
		Hazard statement	May explode in fire
Division 1.6	According to the results of the test in Part I of the Manual of	Symbol	1.6
	Tests and Criteria.	Signal word	No signal word
		Hazard statement	No hazard statement

## page 6 A2.2. Flammable gases (See Chapter 2.2 for details)

Hazard category	Criteria	Hazard communication elements	
1	Gases and gas mixtures, which at 20 °C and a standard pressure of 101.3 kPa:  (a) are ignitable when in a mixture of 13% or less by volume in air; or	Symbol	
	(b) have a flammable range with air of at least 12 percentage points regardless of the lower flammable limit.	Signal word	Danger
		Hazard statement	Extremely flammable gas
	Gases or gas mixtures, other than those of category		No symbol used
2	1, which, at 20 °C and a standard pressure of	Signal word	Warning
	101.3 kPa, have a flammable range while mixed in air.	Hazard statement	Flammable gas

#### **A2.3 Flammable aerosols** (See Chapter 2.3 for details)

Hazard category	Criteria	Hazard communication elements	
	On the basis of its components, of its chemical heat of combustion and, if applicable, of the results of the	Symbol	
1	foam test, for foam aerosols, and of the ignition distance test and enclosed space test, for spray aerosols (see decision logic in para. 62.3.4.1 of Chapter 2.3).	Signal word	Danger
		Hazard statement	Extremely flammable aerosol
2	On the basis of its components, of its chemical heat of combustion and, if applicable, of the results of the foam test, for foam aerosols, and of the ignition		
2	distance test and enclosed space test, for spray aerosols (see decision logic in para. 62.3.4.1 of Chapter 2.3).	Signal word	Warning
		Hazard statement	Flammable aerosol

#### **A2.4 Oxidizing gases** (See Chapter 2.4 for details)

Hazard category	Criteria	Hazard communic	cation elements
1	Any gas which may, generally by providing oxygen, cause or contribute to the combustion of other material more than air does.	Symbol	
		Signal word	Danger
		Hazard statement	May cause or intensify fire; oxidizer

A2.5 Gases under pressure (See Chapter 2.5 for details)

Hazard category	Criteria Hazard communic elements		
		Symbol	
Compressed gas	A gas, which when packaged under pressure is entirely gaseous at -50 °C; including all gases with a critical temperature ≤ -50 °C.	Signal word	Warning
	temperature 2 -50°C.	Hazard statement	Contains gas under pressure; may explode if heated
	A gas which when packaged under pressure, is partially liquid at temperatures above -50 °C. A distinction is made between:	Symbol	
Liquefied gas	i) High pressure liquefied gas: a gas with a critical temperature between -50 °C and +65 °C; and	Signal word	Warning
	<i>ii)</i> Low pressure liquefied gas: a gas with a critical temperature above +65 °C.	Hazard statement	Contains gas under pressure; may explode if heated
	A gas which when packaged is made partially liquid because of its low temperature.	Symbol	
Refrigerated		Signal word	Warning
liquefied gas		Hazard statement	Contains refrigerated gas; may cause cryogenic burns or injury
		Symbol	
Dissolved gas	A gas which when packaged under pressure is dissolved in a liquid phase solvent.	Signal Word	Warning
		Hazard statement	Contains gas under pressure; may explode if heated

#### **A2.6 Flammable liquids** (See Chapter 2.6 for details)

Hazard category	CRITERIA	Hazard communication elements	
1	Flash point < 23 °C and	Symbol	<b>*</b>
	initial boiling point ≤ 35 °C	Signal word	Danger
		Hazard statement	Extremely flammable liquid and vapour
2	Flash point < 23 °C and initial boiling point >35 °C	Symbol	<b>*</b>
2		Signal word	Danger
		Hazard statement	Highly flammable liquid and vapour
3	Flash point ≥ 23 °C and ≤ 60 °C	Symbol	<b>₩</b>
	7 Mon point 2 20 °C min 2 °C °C	Signal word	Warning
		Hazard statement	Flammable liquid and vapour
		Symbol	No symbol used
4	Flash point > 60 °C and ≤ 93 °C	Signal word	Warning
		Hazard statement	Combustible liquid

#### Flammable solids (See Chapter 2.7 for details)

Hazard category	Criteri	ia	Hazard communicati	ion elements
1	Burning rate test:  Substances other than metal powders:  - wetted zone does not stop fire and - burning time < 45 seconds or burning rate > 2.2 mm/s  Metal powders: - burning time ≤ 5 minutes	Symbol		
		Signal word	Danger	
		Hazard statement	Flammable solid	
	4 minutes and	the fire for at least	Symbol	
2	_		Signal word	Warning
	- burning time	> 5 minutes ≤ 10 minutes	Hazard statement	Flammable solid

#### **A2.8** Self-reactive substances (See Chapter 2.8 for details)

Hazard category	Criteria	Hazard communication elements	
	According to the results of tests in the Manual of Tests and Criteria, Part II and the	Symbol	
Type A	application of the decision logic under	Signal word	Danger
	<del>para.6</del> 2.8.4.1 of Chapter 2.8.	Hazard statement	Heating may cause an explosion
Type B	Manual of Tests and Criteria Part II and the	Symbol	
JF	application of the decision logic under para. 2.8.4.1 6 of Chapter 2.8.	Signal word	Danger
		Hazard statement	Heating may cause a fire or explosion
Type C	According to the results of tests in the Manual of Tests and Criteria, Part II and the application of the decision logic under para. 2.8.4.1 6 of Chapter 2.8.	Symbol	
and D		Signal word	Danger
		Hazard statement	Heating may cause a fire
Type E and F	According to the results of tests in the Manual of Tests and Criteria, Part II and the application of the decision logic under para.	Symbol	
	2.8.4.1 6 of Chapter 2.8.	Signal word	Warning
		Hazard statement	Heating may cause a fire
	According to the results of tests in the	Signal word	There are no label elements
Type G	Manual of Tests and Criteria, Part II and the	Symbol	There are no label element allocated to this hazard
app	application of the decision logic under para. 2.8.4.1 6 of Chapter 2.8.	Hazard statement	category.

#### **A2.9 Pyrophoric liquids** (See Chapter 2.9 for details)

Hazard category	Criteria	Hazard communication elements	
	The liquid ignites within 5 min when added to an inert carrier and exposed to air, or it ignites or chars a filter paper on contact with air within 5 min.	Symbol	
l I	with all within 3 mm.	Signal word	Danger
		Hazard statement	Catches fire spontaneously if exposed to air

#### **A2.10 -Pyrophoric solids** (See Chapter 2.10 for details)

Hazard category	Criteria	Hazard communication elements	
		Symbol	
1		Signal word	Danger
		Hazard statement	Catches fire spontaneously if exposed to air

#### **A2.11 Self-heating substances** (See Chapter 2.11 for details)

Hazard category	Criteria	Hazard communication elements	
	A positive result is obtained in a test using	Symbol	
1	a 25 mm sample cube at 140 °C	Signal word	Danger
		Hazard statement	Self-heating; may catch fire
	(a) A positive result is obtained in a test using a 100 mm sample cube at 140 °C and a negative result is obtained in a test using a 25 mm cube sample at 140 °C and the substance is to be packed in packages with a volume of more than 3 m³; or  (b) A positive result is obtained in a test using a 100 mm sample cube at 140 °C and a negative result is obtained in a test using a 25 mm cube sample at 140 °C, a positive result is obtained in a test using a 100 mm cube sample at	Symbol	
2		Signal word	Warning
	<ul> <li>120 °C and the substance is to be packed in packages with a volume of more than 450 litres; or</li> <li>(c) A positive result is obtained in a test using a 100 mm sample cube at 140 °C and a negative result is obtained in a test using a 25 mm cube sample at 140 °C and a positive result is obtained in a test using a 100 mm cube sample at 100 °C</li> </ul>	Hazard statement	Self-heating in large quantities; may catch fire

Substances, which on contact with water, emit flammable gases (See Chapter 2.12 for details)

Hazard category	Criteria	Hazard communication elements		
	Any substance which reacts vigorously with water at ambient temperatures and demonstrates generally a tendency for the	Symbol		
1	gas produced to ignite spontaneously, or which reacts readily with water at ambient	Signal word	Danger	
1	temperatures such that the rate of evolution of flammable gas is equal to or greater than 10 litres per kilogram of substance over any one minute.	Hazard statement	In contact with water releases flammable gases which may ignite spontaneously	
2	Any substance which reacts readily with water at ambient temperatures such that the maximum rate of evolution of flammable gas is equal to or greater than 20 litres per kilogram of substance per hour, and which does not meet the criteria for category 1.	Symbol		
		Signal word	Danger	
		Hazard statement	In contact with water releases flammable gases	
	Any substance which reacts slowly with water at ambient temperatures such that the maximum rate of evolution of flammable	Symbol		
	gas is equal to or greater than 1 litre per kilogram of substance per hour, and which	Signal word	Warning	
	does not meet the criteria for categories 1 and 2.	Hazard statement	In contact with water releases flammable gases	

#### **A2.13 Oxidizing liquids** (See Chapter 2.13 for details)

Hazard category	Criteria	Hazard communication elements		
1	Any substance which, in the 1:1 mixture, by mass, of substance and cellulose tested, spontaneously ignites; or the mean pressure rise time of a 1:1 mixture, by mass, of	Symbol		
	substance and cellulose is less than that of a	Signal word	Danger	
	1:1 mixture, by mass, of 50% perchloric acid and cellulose.	Hazard statement	May cause fire or explosion; strong oxidizer.	
2	Any substance which, in the 1:1 mixture, by mass, of substance and cellulose tested, exhibits a mean pressure rise time less than or equal to the mean pressure rise time of a 1:1 mixture, by mass, of 40% aqueous sodium chlorate solution and cellulose; and the criteria for category 1 are not met.	Symbol		
		Signal word	Danger	
		Hazard statement	May intensify fire; oxidizer.	
Any substance which, in the 1:1 mixture, by mass, of substance and cellulose tested, exhibits a mean pressure rise time less than or equal to the mean pressure rise time of a 1:1		Symbol		
	mixture, by mass, of 65% aqueous nitric acid	Signal word	Warning	
	and cellulose; and the criteria for categories 1 and 2 are not met.	Hazard statement	May intensify fire; oxidizer.	

# (Annex 2) page 16 A2.14 Oxidizing solids (See Chapter 2.14 for details)

Hazard category	Criteria	Hazard communicat	tion elements
1	Any substance which, in the 4:1 or 1:1 sample-to-cellulose ratio (by mass) tested, exhibits a mean burning time less than the mean burning time of a 3:2	Symbol	
	mixture, by mass, of potassium bromate and cellulose.	Signal word	Danger
		Hazard statement	May cause fire or explosion; strong oxidizer
2	Any substance which, in the 4:1 or 1:1 sample-to-cellulose ratio (by mass) tested, exhibits a mean burning time equal to or less than the mean burning time of a 2:3 mixture (by mass) of	Symbol	
	potassium bromate and cellulose and the	Signal word	Danger
	criteria for category 1 are not met.	Hazard statement	May intensify fire; oxidizer
3	Any substance which, in the 4:1 or 1:1 sample-to-cellulose ratio (by mass) tested, exhibits a mean burning time equal to or less than the mean burning time of a 3:7 mixture (by mass) of	Symbol	
	potassium bromate and cellulose and the	Signal word	Warning
	criteria for categories 1 and 2 are not met.	Hazard statement	May intensify fire; oxidizer

#### **A2.15 Organic peroxides** (See Chapter 2.15 for details)

Hazard category	Criteria	Hazard communication elements		
Type A	According to the results of test series A to H in the Manual of Tests and Criteria, Part II and the application of the decision logic under para. 5-2.15.4.1 of Chapter 2.15.	Symbol		
Type II		Signal word	Danger	
		Hazard statement	Heating may cause an explosion	
Туре В	According to the results of test series A to H in the Manual of Tests and Criteria, Part II and the application of the decision logic under para. 2.15.4.1 5 of Chapter 2.15.	Symbol		
		Signal word	Danger	
		Hazard statement	Heating may cause a fire or explosion	
Type C	According to the results of test series A to H in the Manual of Tests and Criteria, Part II and the application of the decision logic under para. 2.15.4.1 § of Chapter 2.15.	Symbol		
-		Signal word	Danger	
		Hazard statement	Heating may cause a fire	
Type E and F	According to the results of test series A to H in the Manual of Tests and Criteria, Part II and the application of the decision logic	Symbol		
	under para. 2.15.4.1 5 of Chapter 2.15.	Signal word	Warning	
		Hazard statement	Heating may cause a fire	
	According to the results of test series A to	Signal word	There are no label elements	
Type G	H in the Manual of Tests and Criteria, Part II and the application of the decision logic	Symbol	allocated to this hazard	
	under para 2.15.4.1 5 of Chapter 2.15.	Hazard statement	category.	

## (Annex 2) page 18 A2.16 Corrosive to metals (See Chapter 2.16 for details)

Hazard category	Criteria	Hazard communication elements		
1	Corrosion rate on steel or aluminium surfaces exceeding 6.25 mm per year at a	Symbol	Mon Salar	
	test temperature of 55 °C.	Signal word	Warning	
		Hazard statement	May be corrosive to metals	

#### **A2.17 Acute toxicity** (See Chapter 3.1 for details)

Hazard category	Criteria	Hazard communication elements		
	$LD_{50} \le 5$ mg/kg bodyweight (oral) $LD_{50} \le 50$ mg/kg bodyweight (dermal)	Symbol		
1	$LC_{50} \le 0.5 \text{ (mg/l) (vapour)}$ $LC_{50} \le 0.05 \text{ (mg/l) (dust,mist)}$	Signal word	Danger	
		Hazard statement	Fatal if swallowed. (oral)  Fatal in contact with skin (dermal)  Fatal if inhaled (gas, vapour, dust, mist)	
	LD <sub>50</sub> between 5 and less than 50 mg/kg bodyweight (oral)  LD50 between 50 and less than 200 mg/kg	Symbol		
2	bodyweight (dermal)	Signal word	Danger	
	LC50 between 100 and less than 500 ppm (gas) LC50 between 0.5 and less than 2.0 (mg/l) (vapour) LC50 between 0.05 and less than 0.5 (mg/l) (dust, mist)	Hazard Statement	Fatal if swallowed. (oral)  Fatal in contact with skin (dermal)  Fatal if inhaled (gas, vapour, dust, mist)	
	LD <sub>50</sub> between 50 and less than 300 mg/kg bodyweight (oral) LD <sub>50</sub> between 200 and less than 1000 mg/kg	Symbol		
3	bodyweight (dermal)	Signal word	Danger	
	LC <sub>50</sub> between 500 and less than 2500 ppm (gas)	Hazard statement	Toxic if swallowed. (oral)	
	$LC_{50}$ between 2.0 and less than 10.0 (mg/l) (vapour) $LC_{50}$ between 0.5 and less than 1.0 (mg/l) (dust, mist)		Toxic in contact with skin (dermal)  Toxic if inhaled (gas, vapour, dust, mist)	
		<u>C</u>	ontinued on next page	

#### UN/SCEGHS/3/INF.5/Add.6

(Annex 2) page 20

Hazard	Criteria	Hazard communication elements		
category (cont'd)				
	LD <sub>50</sub> between 300 and less than 2000 mg/kg bodyweight (oral) LD <sub>50</sub> between 1000 and less than 2000 mg/kg bodyweight (dermal)	Symbol		
4	$LC_{50}$ between 2500 and less than 5000 ppm (gas)	Signal word	Warning	
	LC50 between 10.0 and less than 20.0 (mg/l) (vapour)  LC50 between 1.0 and less than 5.0 (mg/l) (dust, mist)		Harmful if swallowed. (oral)	
		Hazard statement	Harmful in contact with skin (dermal) Harmful if inhaled (gas, vapour, dust, mist)	
		Symbol	No symbol	
	LD <sub>50</sub> between 2000 and 5000 (oral or dermal)	Signal word	Warning	
5	For gases, vapours, dusts, mists, LC <sub>50</sub> in the equivalent range of the oral and dermal LD <sub>50</sub> (i.e., between 2000 and 5000 mg/kg bodyweight)  See also the additional criteria  Indication of significant effect in humans Any mortality at Category 4 Significant clinical signs at Category 4 Indication from other studies	Hazard statement	May be harmful if swallowed (oral)  May be harmful in contact with skin (dermal)  May be harmful if inhaled (gas, vapour, dust, mist)	

#### **A2.18 Skin corrosion/irritation** (See Chapter 3.2 for details)

Hazard category	Criteria		ommunication ments
	<ul> <li>1. For Substances and Tested Mixtures:</li> <li>Human experience showing irreversible damage to the skin;</li> <li>Structure/activity or structure property relationship to a substance or mixture already classified as corrosive;</li> <li>pH extremes of ≤ 2 and ≥ 11.5 including</li> </ul>	Symbol	
1	<ul><li>acid/alkali reserve capacity;</li><li>Positive results in a valid and accepted <i>in vitro</i></li></ul>	Signal word	Danger
Corrosive Including sub- categories A, B, and C;	<ul> <li>Animal experience or test data that indicate that the substance/mixture causes irreversible damage to the skin following exposure of up to 4 hours (See Table 43.2.1)</li> </ul>	Hazard statement	Causes severe skin burns and eye damage
see Chapter 3.2, Table	2. <i>If data for a mixture are not available</i> , use bridging principles in paragraphs 15-21sub-section 3.2.3.2.		
<u> 4 3.2.1</u>	3. If bridging principles do not apply,		
	<ul> <li>(a) For mixtures where substances can be added:         Classify as corrosive if the sum of the         concentrations of corrosive substances in the         mixture is ≥ 5% (for substances with additivity);         or</li> </ul>		
	(b) For mixtures where substances cannot be added: ≥ 1%. See paragraph 253.2.3.3.4.		

#### UN/SCEGHS/3/INF.5/Add.6

(Annex 2) page 22

Hazard category (cont'd)	Criteria	Hazard communication elements	
	For Substances and Tested Mixtures     Human experience or data showing reversible damage to the skin following exposure of up to 4 hours;     Structure/activity or structure property	Symbol	
	<ul> <li>relationship to a substance or mixture already classified as an irritant;</li> <li>Positive results in a valid and accepted <i>in vitro</i> dermal irritation test; or</li> </ul>	Signal word	Warning
2 Irritant	<ul> <li>Animal experience or test data that indicate that the substance/mixture causes reversible damage to the skin following exposure of up to 4 hours, mean value of ≥ 2.3 &lt; 4.0 for erythema/eschar or for oedema, or inflammation that persists to the end of the observation period, in 2 of 3 tested animals (Table 23.2.2).</li> </ul>	Hazard statement	Causes skin irritation
(applies to all authorities)	<ol> <li>If data for a mixture are not available, use bridging principles in paragraphs 15-21sub-section 3.2.3.2.</li> <li>If bridging principals do not apply, classify as an irritant if:         <ul> <li>(a) For mixtures where substances can be added: the sum of concentrations of corrosive substances in the mixture is ≥ 1% but ≤ 5%; the sum of the concentrations of irritant substances is ≥ 10%; or the sum of (10 x the concentrations of corrosive ingredients) + (the concentrations of irritant ingredients) is ≥ 10%; or</li> <li>(b) For mixtures where substances cannot be added: ≥ 3%. (See paragraph 253.2.3.3.4)</li> </ul> </li> </ol>		

Hazard	Criteria	Hazard comm	unication
category	Cinteria	elemen	
(cont'd)			
	1. For Substances and Tested Mixtures	Symbol	None
	Animal experience or test data that indicates that the substance/mixture causes reversible damage	Signal word	Warning
	to the skin following exposure of up to 4 hours, mean value of $\geq 1.5 < 2.3$ for erythema/eschar in 2 of 3 tested animals (See Table $\frac{23.2.2}{}$ )	Hazard statement	Causes mild skin
	2. <i>If data for a mixture are not available</i> and the bridging principles in paragraphs 15-21sub-section 3.2.3.2.		irritation
3 Mild	3. <i>If bridging principles do not apply</i> , classify as mild irritant if:		
Mild Irritant (applies to some authorities)	<ul> <li>For mixtures where substances can be added the sum of the concentrations of irritant substances in the mixture is ≥ 1% but ≤ 10%;</li> </ul>		
	<ul> <li>For mixtures where substances cannot be added: the sum of the concentrations of mild irritant substances is ≥ 10%;</li> </ul>		
	• the sum of (10 x the concentrations of corrosive substances) + (the concentrations of irritant substances) is ≥ 1% but ≤ 10%; or		
	• the sum of (10 x the concentrations of corrosive substances) + (the concentrations of irritant substances) + (the concentrations of mild irritant substances) is $\geq 10\%$ .		

**A2.19** Serious eye damage / eye irritation (See Chapter 3.3 for details)

Hazard category	Criteria		ommunication ements	
category	<ol> <li>For Substances and Tested Mixtures</li> <li>Classification as corrosive to skin;</li> <li>Human experience or data showing damage to the eye which is not fully reversible within 21 days;</li> <li>Structure/activity or structure property relationship to a substance or mixture already classified as corrosive;</li> <li>pH extremes of &lt; 2 and &gt; 11.5 including buffering</li> </ol>	Symbol Signal	Danger	
1 Irrever- sible Effects	<ul> <li>Positive results in a valid and accepted in vitro test to assess severe damage to eyes; or</li> <li>Animal experience or test data that the substance or mixture produces either (1) in at least one animal, effects on the cornea, iris or conjunctiva that are not expected to reverse or have not reversed; or (2) in at least 2 of 3 tested animals a positive response of corneal opacity ≥ 3 and/or iritis &gt;1.5. ( See Table +3.3.1)</li> </ul>	Hazard statement	Causes severe eye damage	
	<ol> <li>If data for a mixture are not available, use bridging principles in paragraphs 17-23sub-section 3.3.3.2.</li> <li>If bridging principles do not apply,</li> <li>(a) For mixtures where substances can be added:         <ul> <li>Classify as Category 1 if the sum of the concentrations of substances classified as corrosive to the skin and/or eye Category 1 substances in the mixture is ≥ 3% or</li> <li>(b) For mixtures where substances cannot be added: ≥ 1 See paragraph 273.3.3.3.4.</li> </ul> </li> </ol>			

Hazard	Criteria	Hazard communication	
category		el	ements
(cont'd)			
	<ul> <li>1. Substances and tested mixtures</li> <li>Classification as severe skin irritant;</li> <li>Human experience or data showing production of changes in the eye which are fully reversible within 21 days;</li> <li>Structure/activity or structure property relationship to a substance or mixture already classified as an eye irritant;</li> <li>Positive results in a valid and accepted in vitro eye</li> </ul>	Symbol	
	<ul> <li>irritation test; or</li> <li>Animal experience or test data that indicate that the substance/mixture produces a positive response in at least</li> </ul>	Signal word	Warning
2A Irritant	<ul> <li>2 of 3 tested animals of: corneal opacity ≥1, iritis ≥1, or conjunctival edema (chemosis) ≥2 (Table 23.3.2).</li> <li>2. If data for a mixture are not available, use bridging principles in paragraphs 17-23 sub-section 3.3.3.2.</li> </ul>	Hazard statement	Causes severe eye irritation
Irritant	<ul> <li>3. If bridging does not apply, classify as an irritant (2A) if: <ul> <li>(a) For mixtures where substances can be added: the sum of the concentrations of skin and/or eye Category 1 substances in the mixture is ≥ 1% but ≤ 3%; the sum of the concentrations of eye irritant substances is ≥ 10%; or the sum of (10 x the concentrations of of skin and/or eye category 1 substances) + (the concentrations of eye irritants) is ≥ 10%</li> <li>(b) For mixtures where substances cannot be added: the sum of the concentrations of eye irritant ingredients is ≥ 3% (See paragraph 273.3.3.3.4)</li> </ul> </li> </ul>		
	1. For Substances and tested mixtures	Symbol	No symbol
	<ul> <li>Human experience or data showing production of mild eye irritation;</li> <li>Animal experience or test data that indicate that the lesions are fully reversible within 7 days. (See Table 22.2.2.)</li> </ul>	Signal word	Warning
2B Mild Irritant	<ul> <li>are fully reversible within 7 days. (See Table 23.3.2)</li> <li>2. If data for a mixture are not available, use bridging principles in paragraphs 17-23sub-section 3.3.3.2.</li> <li>3. If bridging does not apply, classify as an irritant (2A) if: <ul> <li>(a) (a) For mixtures where substances can be added: the sum of the concentrations of skin and/or eye Category 1 substances in the mixture is ≥ 1% but ≤ 3%; the sum of the concentrations of eye irritant substances is ≥ 10%; or the sum of (10 x the concentrations of -of skin and/or eye category 1 substances) + (the concentrations of eye irritants) is ≥ 10%</li> <li>(b) (b) For mixtures where substances cannot be added: the sum of the concentrations of eye irritant ingredients is ≥ 3% (See paragraph 273.3.3.3.4)</li> </ul> </li> </ul>	Hazard statement	Causes eye irritation

#### **Respiratory sensitiser** (See Chapter 3.4 for details)

Hazard category	Criteria	Hazard communication element	
1	<ol> <li>For Substances and Tested Mixture         If there is human evidence that the individual substance induces specific respiratory hypersensitivity, and/or Where there are positive results from an appropriate animal test     </li> <li>If these mixture meets the criteria set forth in the "Bridging Principles" through one of the following:         <ul> <li>(a) Dilution</li> <li>(b) Batching</li> <li>(c) Substantially Similar Mixture</li> </ul> </li> <li>If bridging principles do not apply, classify if any individual respiratory sensitiser in the mixture has a concentration of:         <ul> <li>≥ 1.0% Solid/Liquid</li> <li>≥ 0.2% Gas</li> </ul> </li> </ol>	Symbol  Signal word  Hazard statement	New Health hazard symbol  Danger  May cause allergic or asthmatic symptoms or breathing difficulties if inhaled

#### **A2.21 Skin sensitiser** (See Chapter 3.4 for details)

Hazard category	Criteria	Hazard communication element	
	For Substances and tested mixture     If there is evidence in humans that the individual substance can induce sensitisation by skin contact in a substantial number of persons, or	Symbol	
1	Where there are positive results from an appropriate animal test  2. <i>If the mixture meets the criteria</i> set forth in the "Bridging"	Signal word	Warning
	Principles" through one of the following:  (a) Dilution (b) Batching (c) Substantially similar mixture  3. If bridging principles do not apply, Classify if any individual skin sensitiser in the mixture has a concentration of: ≥ 1.0% Solid/Liquid/Gas	Hazard Statement	May cause allergic skin reaction

Hazard Category	Criteria for classification	Hazard communication elements	
	Known to induce heritable mutations or regarded as	Symbol	New health hazard symbol
1 4	if it induces heritable mutations in the germ cells of humans (see criteria in paragraphs 5-15 section 3.5.2)	Signal word	Danger
1 <u>A</u>	or mixtures containing ≥0.1 % of such a substance	Hazard statement	May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
		Symbol	New Health hazard symbol
1D	to be regarded as if inducing heritable mutations in the germ cells of humans (see criteria in section	Signal word	<u>Danger</u>
<u>1B</u>	3.5.2) or mixture containing ≥0.1/ of such a substance  Hazard statement  May cause g defects (stat of exposure conclusively that no other of exposure	May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard	
		Symbol	New health
2	Causes concern for man owing to the possibility that it may induce heritable mutations in the germ cells of	Signal word	Warning
	humans (see criteria in paragraphs 5-15 section 3.5.2) or mixtures containing ≥1.0 % of such a substance	Hazard Statement	Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

#### **A2.23** Carcinogenicity (See Chapter 3.6 for details)

Hazard category	Criteria	Hazard communication elements	
		Symbol	New health hazard symbol
1	Known or Presumed Human	Signal word	Danger
(both 1A and 1B)	Carcinogen including mixtures containing ≥ 0.1% of such a substance	Hazard satement	health hazard symbol  Danger  May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard.  New health hazard symbol  Warning  Suspected of causing cancer (state route of
		Symbol	health hazard
	Suspected human carcinogen Including mixtures containing more than $\geq 0.1$ or $\geq 1.0$ %	Signal word	Warning
2	of such a substance (See Notes 1 and 2 in Table +3.6.1 of Chapter 3.6)	Hazard statement	causing cancer

<sup>\*</sup> Some authorities will choose to label according to this provision, others may not.

Hazard category	Criteria	Hazard communication elements	
		Symbol	New health hazard symbol
	V nown or presumed human reproductive toyicants (see	Signal word	Danger
1 (Both 1A and 1B)	criteria in paragraphs 3.7.2.2.1 to 3.7.2.6.0 of Chapter 3.7) or mixtures containing $\geq 0.1\%$ or $\geq 0.3\%$ of such a substance	Hazard statement	May damage fertility or the unborn child (state specific effect if known or route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
		Symbol	New health hazard symbol
		Signal word	Warning
2	Suspected human reproductive toxicants (see criteria in paragraphs $6 - 30 \underline{3.7.2.2.1}$ to $3.7.2.6.0$ of Chapter $3.7$ ) or mixtures containing $\geq 0.1\%$ or $\geq 3.0\%$ of such a substance (See Notes 3 and 4 of Table $4 \underline{3.7.1}$ , Chapter $3.7$ )	Hazard statement	

#### A2.24 (b) Effects on or via lactation (See Chapter 3.???)

Hazard category	Criteria	Hazard communication elements	
Special category		Symbol	No symbol  No signal word  May cause
	Substances which cause concern for the health of breastfed children (see criteria in paragraphs 6-303.7.2.2.1 to 3.7.2.6.0	Signal word	
	and 3.7.3.4 of Chapter 3.7)	Hazard Statement	May cause harm to breast-fed children.

Target organ systemic toxicity following single exposure (See Chapter 3.8 for details)

Hazard category	Criteria	Hazard communication elements	
	Reliable evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or systemic toxicity in humans or animals. May use guidance values in Table $\frac{13.8.1}{0.0000}$ , Category 1 criteria as part of weight of evidence evaluation. May be named for specific organ/system.]  Mixture that lacks sufficient data, but contains Category 1 ingredient at a concentration of $\frac{10.000}{0.00000}$ for some authorities; and $\frac{10.000}{0.00000}$ for all authorities.	Symbol Signal word	New health hazard symbol Danger
1		Hazard statement	Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
		Symbol Signal word	New health hazard symbol
2	Evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or systemic toxicity from animal studies or humans considering weight of evidence and guidance values in Table $\frac{43.8.1}{3.8.1}$ , Category 2 criteria. May be named for specific organ/system affected. Mixture that lacks sufficient data, but contains Category 1 ingredient: $\geq 1$ but $\leq 10\%$ for some authorities; and /or contains Category 2 ingredient: $\geq 1$ to $\leq 10\%$ for some authorities; and $\geq 10\%$ for all authorities	Hazard statement	Warning  May causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Hazard category	Criteria	Hazard communication elements	
	Reliable evidence on the substance or mixture (including bridging) of an adverse effect on specific organ/systems or	Symbol	New health hazard symbol
	systemic toxicity in humans or animals. May use	Signal word	Danger
1	idance values in Table $+3.91$ as part of weight of vidence evaluation. May be named for specific gan/system ixture that lacks sufficient data, but contains Category 1 gredient: $\geq 1$ to $\leq 10\%$ for some authorities; and $\geq 10\%$ r all authorities.	Hazard statement	Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
	Evidence on the substance or mixture (including bridging)	Symbol	New health hazard symbol
	of an adverse effect on specific organ/systems or systemic	Signal word	Warning
2	toxicity from animal studies or humans considering weight of evidence and guidance values in Table 2-3.9.2 criteria. May be named for specific organ/system.  Mixture that lacks sufficient data, but contains Category 1 ingredient: ≥ 1.0 but ≤10% for some authorities (See Note 3 of Table 3.9.33) and /or contains Category 2 ingredient: ≥ 1.0 or ≥10%	Hazard statement	Danger  Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard )  New health hazard symbol