UNITED NATIONS



Distr.

**GENERAL** 

TRANS/WP.29/2005/14 22 December 2004

**ENGLISH** 

Original: ENGLISH and FRENCH

## **ECONOMIC COMMISSION FOR EUROPE**

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29) (One-hundred-and-thirty-fifth session, 8-11 March 2005, agenda item 4.2.11.)

## PROPOSAL FOR DRAFT SUPPLEMENT 8 TO REGULATION No. 50

(Position, stop and direction indicator lamps for motorcycles)

Transmitted by the Working Party on Lighting and Light-Signalling (GRE)

<u>Note</u>: The text reproduced below was adopted by GRE at its fifty-third session and is transmitted for consideration to WP.29 and AC.1. It is based on document TRANS/WP.29/GRE/2004/26, not amended (TRANS/WP.29/GRE/53, para. 70).

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user.

Documents are also available via the INTERNET:

http://www.unece.org/trans/main/welcwp29.htm

<u>Paragraphs 7.4.1., 7.4.1.1., 7.4.1.2.</u> and 7.4.1.3., delete the reference to footnote <u>3</u>/.

Footnote 3/, should be deleted.

Insert new paragraphs 7.11., 7.11.1. and 7.11.2., to read:

- "7.11. Maximum values of front direction indicator lamps
- 7.11.1. For devices of categories 11 and 11a, the intensity of the the light emitted outside the zone defined by the measuring points  $\pm$  10 degrees H and  $\pm$  10 degrees V (10 degrees-field) shall not exceed the following values:

| Direction indicator of category | Maximum values in cd outside the 10 degrees-field |   |
|---------------------------------|---|---|
|                                 | Single lamp                                       | Single lamp containing more than one light source |
| 11                              | 400   | 560   |
| 11a                             | 400   | 560   |

Between the boundaries of the 10 degrees-field ( $\pm$  10 degrees H and  $\pm$  10 degrees V) and the 5 degrees-field ( $\pm$  5 degrees H and  $\pm$  5 degrees V), the maximum admissible values of the intensities are linearly increased up to the values as defined in paragraphs 7.4.1. and 7.4.1.1.;

7.11.2. For devices of categories 11b and 11c, the intensity of the light emitted outside the zone defined by the measuring points  $\pm$  15 degrees H and  $\pm$  15 degrees V (15 degrees-field) shall not exceed the following values:

| Direction indicator of category | Maximum values in cd outside the 15 degrees-field |   |
|---------------------------------|---|---|
|                                 | Single lamp                                       | Single lamp containing more than one light source |
| 11b                             | 250   | 350   |
| 11c                             | 400   | 560   |

Between the boundaries of the 15 degrees-field ( $\pm$  15 degrees H and  $\pm$  15 degrees V) and the 5 degrees-field ( $\pm$  5 degrees H and  $\pm$  5 degrees V), the maximum values are increased linearly up to the values as defined in paragraphs 7.4.1.2. and 7.4.1.3."