Proposed amendments to ECE/TRANS/WP29/GRE/2007/55

Paragraph 5.7., amend to read:

- "5.7. <u>Grouped, combined or reciprocally incorporated lamps</u>
- 5.7.1. Lamps may be grouped, combined or reciprocally incorporated with one another provided that all requirements regarding colour, position, orientation, geometric visibility, electrical connections and other requirements, if any, are fulfilled.
- 5.7.1.1. The photometric and colorimetric requirements of a lamp shall be fulfilled when all other **lamps**/functions are switched OFF.

However, when a front or rear position lamp is reciprocally incorporated with one or more other function(s), the requirements regarding colour of each of these other functions shall be fulfilled when the reciprocally incorporated function(s) and the front or rear position lamps are switched ON, except in the case where provisions of paragraph 5.11.2. are fulfilled.

5.7.1.2. However, Where stop lamps and direction indicator lamps, are grouped, any horizontal or vertical straight line..."

Paragraph 5.11., amend to read:

"5.11. The electrical connections must be such that the front and rear position lamps, the end-outline marker lamps, if they exist, the side-marker lamps, if they exist, and the rear registration plate lamp can only be switched **ON** and **OFF** simultaneously. This condition does not apply when using front and rear position lamps, as well as side marker lamps when combined or reciprocally incorporated with said lamps, as parking lamps and when side marker lamps are permitted to flash.

However, when front or rear position lamps are reciprocally incorporated with another lamp/function, the respective front or rear position lamp may be switched off and substituted by such lamp/function, provided that the substituting lamp/function meets the following requirements:

(a) geometric visibility of the respective position lamp;
(b) minimum photometric values according to the angles of light distribution of the respective position lamp."

- **5.11.1.** This condition does not apply:
 - (a) when front and rear position lamps **are switched ON**, as well as side-marker lamps when combined or reciprocally incorporated with said lamps, as parking lamps; or
 - (b) when side-marker lamps are permitted to flash.

- **5.11.2.** However, when front or rear position lamps are reciprocally incorporated with another lamp/function, the respective front or rear position lamp, [or the respective part of the front or rear position lamp,] may be switched OFF and substituted by such lamp/function, provided that the substituting lamp/function meets the following requirements:
 - (a) geometric visibility of the respective position lamp; and
 - (b) minimum photometric values according to the angles of light distribution of the respective position lamp.

Paragraph 5.24., amend to read:

"5.24. Any temporary fail-safe replacement of the light-signalling function of a rear position lamp is allowed, provided that the replacement function in case of a failure is similar in colour, main intensity and position to the function that has ceased to operate and provided that the replacement device remains operational in its original safety function. During replacement, a tell-tale on the dashboard (see paragraph 2.18. of this Regulation) shall indicate occurrence of a temporary replacement and need for repair."

JUSTIFICATION

OICA understands that the intention of document ECE/TRANS/GRE/2007/55 is that the provisions of paragraph 5.7.1.1. and paragraph 5.11 should be alternative to each other.

However this is not entirely clear from the proposed text.

The OICA proposed text is intended to clarify the original intention by clearly specifying the alternatives.

The text shown in [square brackets] is intended to clarify that where only part of a position lamp is reciprocally incorporated with another lamp or function, only that part which is reciprocally incorporated needs to be switched off when the other lamp or function is operating. However GRE may conclude that this is already clear from the current text and the additional text proposed by OICA can be deleted.

- - - - -