

Economic and Social Council

Distr. GENERAL

ECE/TRANS/WP.29/2008/33 13 December 2007

ENGLISH Original: ENGLISH AND FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations

One-hundred-and-forty-fourth session Geneva, 11-14 March 2008 Item 4.2.34. of the provisional agenda

1958 AGREEMENT

Consideration of draft amendments to existing Regulations

<u>Proposal for Corrigendum 1 to Supplement 3 to the Regulation No. 104</u> (Retro-reflecting markings for heavy and long vehicles and their trailers)

Submitted by the Working Party on Lighting and Light-Signalling (GRE) */

The text reproduced below was adopted by GRE at its fifty-eighth session. It is based on ECE/TRANS/WP.29/GRE/2006/59, not amended. It is submitted to WP.29 and AC.1 for consideration (ECE/TRANS/WP.29/GRE/58, para. 28).

^{*/} In accordance with the programme of work of the Inland Transport Committee for 2006-2010 (ECE/TRANS/166/Add.1, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance performance of vehicles. The present document is submitted in conformity with that mandate.

ECE/TRANS/WP.29/2008/33 page 2

Annex 8

Paragraph 5.2.1., amend to read:

- "5.2.1 When subjected to a continuous spraying action for 60 seconds on the test component in its normal mounting conditions, a test sample shall show no damage to the retro-reflective surface or delamination from the substrate or separation from the sample mounting surface under the following set-up parameters:
 - (a) Water/wash solution pressure 8 ± 0.2 MPa;
 - (b) Water/wash solution temperature 60° 5 °C;
 - (c) Water/wash solution flow rate 7 ± 1 l/min;
 - (d) The tip of the cleaning wand to be positioned at distance of 600 ± 20 mm away from the retro-reflective surface;
 - (e) Cleaning wand to be held at no greater angle than 45 degrees from perpendicular to the retro-reflective surface;
 - (f) 40 degree nozzle creating wide fan pattern."

- - - - -