

# Economic and Social Council

Distr. GENERAL

ECE/TRANS/WP.29/2009/68 9 April 2009

ENGLISH Original: ENGLISH AND FRENCH

## ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations

One-hundred-and-forty-eighth session Geneva, 23 - 26 June 2009 Item 4.2.21 of the provisional agenda

## 1958 AGREEMENT

Consideration of draft amendments to existing Regulations

Proposal for Supplement 8 to Regulation No. 106 (Tyres for agricultural vehicles)

Submitted by the Working Party on Brakes and Running Gear \*/

The text reproduced below was adopted by the Working Party on Brakes and Running Gear (GRRF) at its sixty-fifth session. It is based on ECE/TRANS/WP.29/GRRF/2009/16, not amended, and ECE/TRANS/WP.29/GRRF/2007/20/Rev.1, as amended by GRRF-65-17. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee (AC.1) for consideration (ECE/TRANS/WP.29/GRRF/65, para. 42).

 $<sup>\</sup>frac{*}{}$  In accordance with the programme of work of the Inland Transport Committee for 2006-2010 (ECE/TRANS/166/Add.1, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance performance of vehicles. The present document is submitted in conformity with that mandate.

# ECE/TRANS/WP.29/2009/68 page 2

Paragraph 2.1.3., amend to read:

- "2.1.3. category of use:
  - (a) Tractor Steering wheel;
  - (b) Tractor Drive wheel standard tread;
  - (c) Tractor Drive wheel special tread;
  - (d) Implement traction;
  - (e) Implement trailer;
  - (f) Implement mixed applications;
  - (g) Forestry machines standard tread;
  - (h) Forestry machines special tread."

Paragraph 2.20., amend to read:

"2.20. ..... driven axles of agricultural tractors ......"

Insert a new paragraph 2.41., to read:

"2.41. Forestry tyre: means a tyre designed to be fitted to machines or equipments used in forestry applications."

Paragraph 3.1.8., amend to read:

"3.1.8. the inscriptions 'LS-1', 'LS-2', 'LS-3' or 'LS-4' in the case of tyres for forestry machines."

Insert a new paragraph 3.1.8.1., to read:

"3.1.8.1. 'LS-3' identifies special tread tyres."

Paragraph 5.3., amend to read:

"5.3. Notice of approval or extension or refusal or withdrawal of approval or production definitively discontinued of a type of pneumatic tyre pursuant to this Regulation shall be communicated to the Parties to the 1958 Agreement which apply this Regulation, by means of a form conforming to the model in Annex 1 to this Regulation."

Paragraph 5.4.2., amend to read:

"5.4.2. The number of this Regulation, followed by the letter "R", a dash and the type approval number."

Paragraph 6.4.2., amend the second and third row in the table, to read:

"Tractor drive wheels and forestry machines - normal", "Tractor drive wheels and forestry machines – special".

Annex 3


<u>Part A</u>, amend the title to read:

#### "PART A: DRIVE WHEEL TYRES FOR AGRICULTURAL TRACTORS"

Add a new part D, to read:

#### "PART D: TYRES FOR FORESTRY MACHINES

Example of the markings to be borne by types of tyres complying with this Regulation



MINIMUM HEIGHTS OF MARKINGS: b: 9 mm c: 4 mm

These markings define a tyre for forestry machines (LS):

- (a) having a nominal section width of 600,
- (b) having a nominal aspect ratio of 55,
- (c) of diagonal ply structure (-),
- (d) having a nominal rim diameter of 673 mm for which the code is 26.5,
- (e) having an intermediate tread ("LS-2"),
- (f) having a load capacity of 3750 kg, corresponding to load index 154 in Annex 4,
- (g) classified in the speed category A8 (reference speed 40 km/h),
- (h) for fitting without an inner tube ("tubeless"),
- (i) manufactured during the twenty-fifth week of the year 2006 (see paragraph 3.2. of the Regulation).

The positioning and order of the markings constituting the tyre designation are as follows:

- (a) the size designation, comprising the nominal section width, the nominal aspect ratio, the type of structure symbol (where applicable) and the nominal rim diameter, must be grouped as shown in the above example: 600/55 26.5;
- (b) the inscription 'LS', followed by the number 1, 2, 3 or 4 as appropriate, is placed after the size designation, as shown in the above example: LS-2;
- (c) the service description (load index and the speed category symbol) is placed near the size designation. It may either precede or follow it or be placed above or below it;
- (d) the symbols 'TUBELESS' and the date of production may be at a distance from the size designation."

ECE/TRANS/WP.29/2009/68 page 4

<u>Annex 5,</u> Delete from table 4 all data for the following three tyre size designations: 260/70R16, 260/70R18 and 260/70R20.

Annex 7

"

<u>PART A</u>, amend the title to read:

#### "PART A: DRIVE WHEEL TYRES FOR AGRICULTURAL TRACTORS"

Add a new part D, to read:

#### "PART D: TYRES FOR FORESTRY MACHINES Applicable to tyres classified with categories of use: "Forestry machines" (see paragraph 2.41.)

Variation of load carrying capacity (per cent) for tyres marked with speed category symbol A8

Service Condition	Speed (km/h)	per cent
Road service	20	23
	30	7
	40	[0]

- - - - -