Corrections to ECE/TRANS/WP.29/2011/16 (Regulation No. 123)

A. Proposal

Insert a new paragraph 2.2.2.(l), to read:

"2.2.2.

(l) In the case of adaptation of the driving-beam, which lighting units ⁴ provide or contribute to the gradual adaptation of the driving-beam and of the sensor system along with the technical characteristics relevant to their operation."

Annex 3, table 1, correct to read:

"Table 1:...

			P	Position /deg	s s				passin	passing beam				
E	oled re	tabled requirements expressed in cd	horizontal	ontal	vertical	cla	class C	cla	class V	cla	class E	cl	class W	
	No	Element	at/ from	to	at	min	max	min	max	min	max	min	max	
L.	-	B50L #	L 3.43		U 0.57	50 4/	350	90	350	90	625 8/	90	625	
	2	₩ VH	Λ		Н	50 4/	625	50	625	50		50		
	3	BR #	R 2.5		U 1	50 4/	1750	50	880	50	1750	50	2650	
	4	Segment BRR #	R 8	R 20	U 0.57	50 4/	3550		880		3550		5300	
	5	Segment BLL	8 T	L 20	U 0.57	50 4/	625		880		088		088	
	9	Ь	L 7		Н	63						63		
	7	Zone III (as specified by Table 3 of this annex)					625		625		880		088	
7	8a	S50, S50LL, S50RR 5/			U 4	63 7/				63 7/		// 89		
₹ 1.11	9a	S100, S100LL,S100RR 5/			U 2	125 7/				125 7/		1257/		
ьa	10	50 R	R 1.72		D 0.86			5100						
	Ξ	75 R	R 1.15		D 0.57	10100				15200		20300		
	12	50 V	Λ		98.0 Q	5100		5100		10100		10100		
	13	50 L	L 3.43		D 0.86	3550	13200 9/	3550	13200 9/	0089		0089	26400	/6
	14	25 LL	L 16		D 1.72	1180		845		1180		3400		
	15	25 RR	R 11		D 1.72	1180		845		1180		3400		
	16	Segment 20 and below it	L 3.5	Λ	D 2								17600	2/
	17	Segment 10 and below it	L 4.5	R 2.0	D 4		12300 1/		12300 1/		12300 1/		7100	2
	18	Emax <u>3</u> /				16900	44100	8400	44100	16900	79300 8/	29530	70500	2
Par	t B (be	Part B (bending modes): Table 1 Part A applies, however with the lines Nos. 1, 2, 7, 13 and 18 being replaced by those listed hereunder	r with the	lines No	3. 1, 2, 7, 1	3 and 18 b	eing replace	ed by thos	se listed here	under				
	1	B50L 44	L 3.43		U 0.57	50 4/	530		530				790	
	2	HV #				50 4/	880		880					
H III	7	Zone III (as specified by Table 3 of this annex)					880		880		880		088	
ď	13	50L	L 3.43		D 0.86	1700		1700		3400		3400		
	18	Emax <u>6</u> /				10100	44100	5100	44100	10100	79300 8/	20300	70500	2/
۱۰														

Annex 3, table 1, footnote ⁶, amend to read:

[&]quot;⁶ Position requirements as indicated in paragraph 6.2.5.2. of this Regulation"

A. Justification

ECE/TRANS/WP.29/2011/16 is also based on:

- (a) ECE/TRANS/WP.29/GRE/2010/42 adopted by GRE at its sixty-fourth session in October 2010, as amended by Annex IV to the report (see ECE/TRANS/WP.29/GRE/64, para. 19).
- (b) ECE/TRANS/WP.29/GRE/2010/50 adopted by GRE at its sixty-fourth session in October 2010, as amended by Annex XII to the report (see ECE/TRANS/WP.29/GRE/64, para. 38).

However, the amendments above reproduced have not been included in ECE/TRANS/WP.29/2011/33. This informal document aims at correcting that error.