



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/1014
21 April 2004

ENGLISH
Original: ENGLISH and FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)

CORRIGENDUM 1 TO SUPPLEMENT 2 TO REGULATION No. 113

(Headlamps emitting a symmetrical passing beam)

Note: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its twenty-sixth session, following the recommendation by WP.29 at its one-hundred-and-thirty-second session. It is based on document TRANS/WP.29/2004/10, not amended (TRANS/WP.29/992, para. 79).

Paragraph 6.3.2.2., correct to read:

"6.3.2.2. Starting from point HV, horizontally to the right and left, the illumination shall be not less than 12 lux for Class B and C headlamp, and 24 lux for Class D headlamp to a distance of 1125 mm and not less than 3 lux for Class B and C headlamp, and 6 lux for Class D headlamp to a distance of 2250 mm.

In the case of a Class C and D headlamp, the intensities shall conform to the tables A or B in annex 3. Table A applies in the case where a primary driving beam is being produced with a single light source. Table B applies in the case where the driving beam is being produced by a secondary driving beam headlamp operated with a harmonized passing beam headlamp or a primary driving beam headlamp."
