

## Proposal for amendments to ECE/TRANS/WP.29/GRRF/2014/2

### I. Proposal

Insert a new paragraph 2.15.9., to read:

**"2.15.9-11** the letters "IND" after the nominal rim diameter marking in case of tyres for construction application (industrial tractors)"

Annex 5,

Add a new table 8, to read:

**"Table 8 – Tyres for Construction Applications (Industrial Tractors)**

Tyre Size Designation	Theoretical rim width code (A1)	Nominal section Width (S1) (mm)		Overall Diameter (D) (mm)		Nominal rim Diameter (d) Theoretical rim-width (mm)
		Overall Diameter (D) (mm)		Nominal rim Diameter (d) Tyre-Size Designation		
		Radial	Diagonal	Radial	Diagonal	(mm)
14.9-24	13	378	378	1 245	1 240	610
14.9-28	13	378	378	1 350	1 345	711
16.9-24	15	429	429	1 320	1 310	610
16.9-28	15	429	429	1 420	1 410	711
16.9-34	15		429		1 560	864
17.5L-24	15	445	445	1 250	1 241	610
18.4-24	16	467	467	1 395	1 375	610
18.4-26	16		467		1 425	660
18.4-28	16	467	467	1 490	1 477	711
18.4-30	16		467		1 525	762
19.5L-24	17	495	495	1 320	1 314	610
21L-24	18	533	533	1 395	1 378	610
23.1-26	20		587		1 580	660

## **II. Justification**

Editorial corrections.

---