UNITED NATIONS



## **Economic and Social Council**

Distr. GENERAL

TRANS/WP.29/570 7 July 1997

ENGLISH

Original: ENGLISH

and FRENCH

## **ECONOMIC COMMISSION FOR EUROPE**

INLAND TRANSPORT COMMITTEE

Working Party on the Construction of Vehicles

DRAFT SUPPLEMENT 3 TO THE 01 SERIES OF AMENDMENTS TO REGULATION No. 57

(Headlamps for motorcycles)

Note: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its sixth session, following the recommendation by the Working Party at its one-hundred-and-twelfth session. It is based on document TRANS/WP.29/R.815, not amended (TRANS/WP.29/566, paras. 61 and 125).

Annex 4, paragraph 1.2.1.1., replace by the following text (including also a new footnote  $\frac{4}{}$ ):

## "1.2.1.1. Test mixture

1.2.1.1.1. For headlamp with the outside lens in glass:

The mixture of water and a polluting agent to be applied to the headlamp shall be composed of:

- 9 parts by weight of silica sand with a particle size of 0-100  $\mu\text{m}\,,$
- 1 part by weight of vegetal carbon dust (beechwood) with a particle size of 0-100  $\mu\text{m}\text{,}$
- 0.2 part by weight of NaCMC 3/, and

an appropriate quantity of distilled water, with a conductivity of  $\bullet$  1 mS/m.

The mixture must not be more than 14 days old.

1.2.1.1.2. For headlamp with outside lens in plastic material:

The mixture of water and polluting agent to be applied to the headlamp shall be composed of:

- 9 parts by weight of silica sand with a particle size of 0-100  $\mu\text{m}\,,$
- 1 part by weight of vegetal carbon dust (beechwood) with a particle size of 0-100  $\mu\text{m},$
- 0.2 part by weight of NaCMC 3/,
- 13 parts by weight of distilled water with a conductivity of  $\cdot$  1 mS/m, and
- $2 \pm 1$  parts by weight of surface-actant. 4/

The mixture must not be more than 14 days old.

4/ The tolerance on quantity is due to the necessity of obtaining a dirt that correctly spreads out on all the plastic lens."

Paragraph 1.2.1.2., the reference to footnote 4/ and footnote 4/, renumber as footnote 5/.

<sup>3/ (</sup>note not modified)