UNITED NATIONS



Economic and Social Council

Distr. GENERAL

TRANS/WP.29/628 2 June 1998

ENGLISH

Original: ENGLISH

and FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

Working Party on the Construction of Vehicles

DRAFT SUPPLEMENT 11 TO REGULATION No. 54

(Pneumatic tyres for commercial vehicles)

<u>Note</u>: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its eighth session, following the recommendation by the Working Party at its one-hundred-and-fourteenth session. It is based on document TRANS/WP.29/1998/5, not amended TRANS/WP.29/609, paras. 73 and 124).

GE.98-

Paragraph 6.1.4.2., amend to read:

"... However, for tyres with nominal section width exceeding 305 mm intended for dual mounting (twinning), the value determined pursuant to paragraph 6.1.1. above shall not be exceeded by more than 2 per cent for radial-ply tyres with nominal aspect ratio higher than 60, or 4 per cent for diagonal (bias-ply) tyres."

Annex 5,

PART I, Table D, delete the following tyre sizes:

"24x 7.50-1	3	31x13.50-15	
27x 8.50-1	4	31x15.50-15	
28x 8.50-1	5	32x11.50-15	<u>*</u> /
29x 9.50-1	5	33x12.50-15	
30x 9.50-1	5	35x12.50-15	
31x10.50-1	5	37x12.50-15	
31x11.50-1	5	37x14.50-15	

 $[\]underline{\star}$ / Erroneously indicated in Regulation No. 54, Revision 1 as "32x11.50-50".

PART II, Table B, insert at the end the following two new tyre sizes:

Tyre size designation	Measuring rim width code	Nominal rim diameter d (mm)	Outer diameter D (mm) <u>2</u> / Normal Snow		Section width S (mm)
<u>=</u> /		G. ()	1101111011	2110 11	<u> </u>
33x9.50 R15LT	7.50	381	826	832	240
35x12.50 R16.5LT	10.00	419	877	883	318